

Non-return damper, light design with lower pressure loss

Frame made of Aluminium C-Profiles, resp. from 1'000mm side length upwards made of galvanized steel, screwed with corner angles – no welds of any kind – suitable for all duct connection flanges. Flanges 36mm or 50mm, depth 165mm. Damper width in 1mm increments, for widths greater than 900mm with intermediate support. Torsion rigid Aluminium single-skin blades 100mm, with changeable EPDM-Sealing, temperature resistant up to 80 °C. With integrated sealings on the sides. Shafts made of Aluminium, pressed into the end of the blades, on both sides in plain bearings made of plastic. Shaft diameter 16mm. Leakage rate according to CEN 1751, Class 3. Pressure resistance against the air flow direction at least 1'200Pa



The pressure relief dampers are suitable for horizontal and vertical air flows. The direction of the air flow **must** be specified. If the air flow is horizontal, the blades need to be horizontal as well.

Function:

The blades are closed in normal position and open with the air current. Because the blades can only be opened in one direction, an airflow in the opposite direction is prevented from happening.

Options (please choose required ones):

- blades coupled with linkage on the outside of the frame
- frame insulated on all 4 sides with mineral wool, placed in second frame and thermally decoupled
- blades insulated
- damper powder coated
- limit switches to detect the closed position
- wire mesh on one or both sides
- air flow vertical, upwards
- air flow vertical, downwards
- combinations with weatherproof louvers
- wall frames or installation clamps

Further Options upon request.